


Pulse Transformers

- Encapsulated Isolation Transformer
- Suitable for Data Interface
- Operating Temp 0°C to 70°C






Electrical Specification @ Ta=25°C




Part No.	Primary OCL mH	Turns Ratio	Interwinding Capacitance pF	Leakage Inductance μH	DCR (Ω)	FIG	SCH
G511	2.00	1:1	25	8.0	1:1	C	1
G516	0.50	1:1.3	32	0.7	1.35:1.35	A	1
G510	0.05	1CT:1CT	18	0.5	1.3:1.3	A	2
G509	0.50	1CT:1CT	32	0.4	1.3:1.3	A	2
G508	2.00	1CT:1CT	37	0.8	2.5:2.5	A	2
G517	1.00	1CT:1.41CT	32	1.5	1.5:1.5	A	2
G515	0.20	2CT:1CT	8	0.8	0.9:0.5	A	2
G512	2.00	2CT:1CT	19	1.8	2.5:1.4	A	2
G503	0.20	1:1:1	18	0.3	0.9:0.9:0.9	A	3
G553	0.20	1:1:1	16	0.5	1.1:1.1:1.1	A	3
G502	0.50	1:1:1	32	0.4	1.3:1.3:1.3	A	3
G513	1.20	1:1:1	25	0.5	0.7:0.7:0.7	A	3
G514	1.20	1:1:1	30	0.7	0.7:0.7:0.7	A	3
G501	2.00	1:1:1	37	0.8	2.5:2.5:2.5	A	3
G500	5.00	1:1:1	60	1.3	3.9:3.9:3.9	A	3
G700	4.00	1:1:1	77	2.2	5.3:5.3:5.3	B	3
G701	10.00	1:1:1	127	3.0	8.9:8.9:8.9	B	3
G557	0.20	2:1:1	10	2.5	1.0:0.7:0.7	A	3
G507	0.50	2:1:1	11	1.1	1.3:0.7:0.7	A	3
G506	2.00	2:1:1	19	1.8	2.5:1.4:1.4	A	3
G505	5.00	2:1:1	33	3.6	3.9:2.0:2.0	A	3

Mechanical Dimensions Inches (mm)

All dimensions are typical, please contact Tamura for tolerances and suggested layout information.



Schematics



TAMURA CORPORATION

43352 Business Park Drive. | P.O. Box 892230 Temecula, CA 92589-2230 | www.tamuracorp.com
 USA | Japan | United Kingdom | Hong Kong
 Tel: 800-872-6624 | Tel: 81 (0)3 3978-2111 | Tel: 44 (0) 1380 731 700 | Tel: 852-2389-4321
 Fax: 909-676-9482 | Fax: 81 (0)3 3923-0230 | Fax: 44 (0) 1380 731 702 | Fax: 852-2341-9689